380 ALPR-READY TRAILER





The trailer is compatible, interchangeably, with the following signage:

- SpeedAlert 18 or 24 (SA18 or SA24) Radar Message Sign
- InstAlert 18 or 24 (IA18 or IA24) Variable Message Sign
- Shield 15 (Sh15) Radar Speed Display
- 5' clearance from the ground to bottom of the sign meets MUTCD minimum requirement

Weight

- 1200 lbs with 900Ah battery capacity and SpeedAlert
 24
- Tongue weight: 50 lbs
- **Dimensions:** 61.5" long x 62.5" wide x 65" high (stowed)
- Simple manual lever lift system for 1-person setup
- Removable tongue for 2" ball, lockable
- Storage for tongue and lift bar in locked battery compartment
- 16 ga. steel locking battery compartment with vented battery chamber, charger/accessories chamber and 1/8" aluminum diamond plate lid
- Continuous weld steel frame, white marine grade powder coat finish
- Additional locking battery box for expanded battery capacity, includes ALPR system equipment area with access panel and optional recessed camera compartment
- Wheels: 12" bolt steel rims with 4.5" bolt circle
- Ground Clearance: 9.75 under axle, 19 under chassis
- · Replaceable steel fenders, weight supporting
- Locking wheel lug bolts, one per wheel, with removal tool
- Axle: 2000# leaf spring
- Jacks: 4, retractable crank type, fully adjustable at each corner, 1500 lb capacity each
- Recessed tail lights and DoT approved lighting
- · Safety chains, 23" with hooks
- DoT approved red/white reflective tape
- License plate holder with light



Trailer Power

- 12 VDC system, standard four pin wiring plug
- 900Ah batteries, (2) 6VDC batteries in series, deep cycle marine (130 lbs per pair, four pairs)
- 40A time delay fuse on battery supply
- 380W solar assist with 30A MPPT solar controller with low voltage disconnect to prevent overcharging and over-discharging
- Solar panels charge while sign stowed or deployed
- 40 Amp 120VAC automatic charger with externally accessible AC connection
- Independent switches to control power to sign and ALPR system separately

Trailer Options

- External camera box (up to two camera capacity)
- Recessed camera compartment
- 30" x 36" speed limit sign and interchangeable digits for 5-65 mph display and locking hitch pin for display and stowing; digit storage in battery compartment
- Red and Blue violator strobe light bar, set to flash above user set speed
- 2 5/16" ball coupler or pintle hook, adjustable height, on removable tongue
- Orange powder coat finish (minimum order quantity)
- Tamper alarm with adjustable sensitivity
- Wheel lock bar
- '7' digit for speed limit sign
- 14" tires and fenders

Warranty

1-year warranty (three months on batteries)



Optional recessed camera compartment









sales@alltrafficsolutions.com



Call us at 866.366.6602

